Xerox® Colour 560/570 Printer
Colour Multifunction Printer

To interactively build and configure your own Xerox® Colour 560/570, please visit **www.buildyourownxerox.com**.

	Xerox® Colour 560 Printer		Xerox® Colour 570 Printer	
Simplex Speeds	**Colour**	**Black and white**	**Colour**	**Black and white**
8.5 x 11 in. / A4				
64 to 105 gsm uncoated	Up to 60 ppm	Up to 65 ppm	Up to 70 ppm	Up to 75 ppm
106 to 176 gsm uncoated	Up to 43 ppm	Up to 65 ppm	Up to 50 ppm	Up to 75 ppm
106 to 150 gsm coated	Up to 43 ppm	Up to 43 ppm	Up to 50 ppm	Up to 50 ppm
151 to 300 gsm uncoated	Up to 30 ppm	Up to 43 ppm	Up to 35 ppm	Up to 50 ppm
151 to 300 coated	Up to 30 ppm	Up to 30 ppm	Up to 35 ppm	Up to 35 ppm
11 x 17 in. / A3				
64 to 105 gsm uncoated	Up to 30 ppm	Up to 33 ppm	Up to 35 ppm	Up to 37 ppm
106 to 176 gsm uncoated	Up to 21 ppm	Up to 33 ppm	Up to 25 ppm	Up to 37 ppm
106 to 150 gsm coated	Up to 21 ppm	Up to 21 ppm	Up to 25 ppm	Up to 25 ppm
151 to 300 gsm uncoated	Up to 14 ppm	Up to 21 ppm	Up to 17 ppm	Up to 25 ppm
151 to 300 coated	Up to 14 ppm	Up to 14 ppm	Up to 17 ppm	Up to 17 ppm
12 x 18 in. / SRA3				
64 to 105 gsm uncoated	Up to 27 ppm	Up to 29 ppm	Up to 30 ppm	Up to 33 ppm
106 to 176 gsm uncoated	Up to 19 ppm	Up to 29 ppm	Up to 19 ppm	Up to 33 ppm
106 to 150 gsm coated	Up to 19 ppm	Up to 19 ppm	Up to 19 ppm	Up to 19 ppm
151 to 300 gsm uncoated	Up to 12 ppm	Up to 19 ppm	Up to 12 ppm	Up to 19 ppm
151 to 300 coated	Up to 12 ppm	Up to 12 ppm	Up to 12 ppm	Up to 12 ppm
Auto Duplex Speeds	**Colour**	**Black and white**	**Colour**	**Black and white**
8.5 x 11 in. / A4 Example: 64 to 105 gsm uncoated	Up to 60 ipm 2-sided 30 sheets per minute	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 35 sheets per minute
11 x 17 in. / A3 Example: 64 to 105 gsm uncoated	Up to 30 ppm 2-sided 15 sheets per minute	Up to 33 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute
Device Specifications				
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis).			
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month (expected regular monthly throughput).			
Technology	Xerox® EA toner with Ultra Low Melt Technology			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan			

Xerox® Colour 560/570 Printer

Accessories	
Optional	Offset Catch Tray High Capacity Feeder 1 Tray Oversized High Capacity Feeder 2 Tray Oversized High Capacity Feeder Interface Module Advanced Finisher Professional Finisher Standard Finisher (requires Interface Module) Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ (requires Interface Module and Standard Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Standard Finisher with Booklet Maker) Convenience Stapler Xerox® Integrated Fiery® Colour Server Xerox® FreeFlow® Print Server EX Print Server, Powered by Fiery Foreign Device Interface Kit PostScript Kit USB Enablement Kit Media Card Reader Scan to Searchable PDF Fax over IP Kit 1 (3 Line Outside N. America) Fax Kits Server Fax Kit Network Accounting Kit Common Access Card Enablement Kit ScanFlowStore Xerox® Scan to PC Desktop® Xerox Secure Access Unified ID System® Equitrac Office®
Electrical Requirements	
North America	Voltage: 110-127V Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A
Accessories North America: Europe:	 Each module requires 120V, 15 A Each module requires 220V, 10 A
Power Consumption	
Running (Average)	1,052 watts (Preliminary value. Pending final report)
Low Power Mode (Average)	< 131 watts (Preliminary value. Pending final report)
Sleep Mode (Average)	1.3 watts (Preliminary value. Pending final report)
Low Power Mode Recovery Time	30 seconds
Operating Environment	
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)
Required Relative Humidity	15% to 85% (no condensation)
Sound Power Levels	Operating 48.8 dB(A), Standby: 40.9dB(A) (Preliminary value. Pending final report)
Weight (approximate base unit only)	604 lb., 273 kg

Dimensions	Width	Depth	Height
Base Unit with Offset Catch Tray	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Advanced Finisher	85.3 in. / 2,166.6 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Professional Finisher	85.3 in. / 2,166.6 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Standard Finisher	97.7 in. / 2481 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Booklet Maker Finisher	122.9 in. / 3121.7 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
GBC® AdvancedPunch™	12 in. / 305 mm	28.5 in. / 724 mm	38.5 in. / 978 mm
Xerox® SquareFold® Trimmer	42 in. / 1066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm
High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm
One Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.9 in. / 785 mm	36.6 in. / 930 mm
Two Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Certifications			
	WHQL certification (depending on print server / controller selected) Citrix IPv6 Ready MEDITECH SAP Common Criteria (Xerox® 560 complete; Xerox® 570 pending) FIPS 140-2 ENERGY STAR® Environmental Choice EPEAT (Bronze) NOM ECO/GOST		
Graphic Arts Credentials			
	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe PostScript 3 (certified) *requires a digital front end (e.g. FreeFlow or EFI)		
Paper Handling			
Duplex Automatic Document Feeder (DADF)			
Capacity	250 sheets of 24 lb. bond / 90 gsm		
Speed	Copy mode: Up to 50 ppm colour / 75 ppm black and white Scanning mode: Up to 50 ppm colour / 80 ppm black and white		
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 to 28 lb. bond / 60 to 105 gsm		
Bypass Tray			
Capacity	Up to 250 sheets		
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in. / 102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)		
Envelope Capacity	30 to 50 envelopes		
Envelope Sizes	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5. Paper Size Default within tools) run flap open at the trail edge) Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in. / 190 x 170 mm to 240 x 173 mm		
Envelope Weights	75 to 90 gsm		

Trays 1 to 4	
Capacity	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4
Weights	18 lb. bond to 80 lb. cover / 64 to 220 gsm (uncoated and coated)
Optional High Capacity Feeder (HCF)	
Capacity	2,000 sheets
Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
Weights	18 lb. bond to 80 lb. cover / 64 to 220 gsm (uncoated and coated)
Optional Oversized High Capacity Feeder (OHCF) – 1 or 2 Tray Options	
Capacity	1 Tray OHCF: 2,000 sheets 2 Tray OHCF: 4,000 sheets
Sizes	1 Tray OHCF: 7.25 x 10.5 in. to 13 x 19 in. / B5 to SRA3 2 Tray OHCF: 4 x 6 in. to 13 x 19 in. / 102 x 152 mm to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)
Total Capacity	
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder)
Automatic Two-Sided	• 65 lb. cover /176 gsm auto duplex for all stocks • 80 lb. / 220 gsm auto duplex for most stocks includes A4 / Letter / A3 / Tabloid (does not include 11 x 17 in. / A3 coated and 12 x 18 in. / SRA3) • 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder
Finishing	
Offset Catch Tray	
Capacity	500-sheet stacking
Optional Advanced Finisher	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Stacking Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	8.5 x 11 in. to 13 x 19 in. / A4 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)
Multiposition Stapling	Up to 50 sheets
Hole-punching North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch Swedish 4-hole Punch (Optional)
Optional Professional Finisher	
Capacity	Top Tray: 500 sheets of 20 lb. / 80 gsm, 8.5 x 11 in. / A4 Stacking Tray: 1,500 sheets of 20 lb. / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 50 sheets
Hole Punching North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Making Capacity: Sizes:	 Bi-fold, saddle stitch booklet maker up to 15 uncoated sheets, 7 sheets at 106 to 176 gsm coated, 5 sheets at 177-220 gsm coated 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3

Optional Standard Finisher (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	 200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Optional Z Fold / C Fold Unit (Optional with Standard Finisher)	
Capacity	30 sheets of 24 lb. bond / 90 gsm, 8.5 x 11 in. / A4
Sizes	8.5 x 11 in. / A4
Weights	Media up to 24 lb. / 90 gsm
Optional Standard Finisher with Booklet Maker (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	 200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated) Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3
Optional GBC® AdvancedPunch (Optional with Standard Finisher – requires Interface Module)	
Punch Configuration Sizes	8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm
Weights	20 lb. bond to 80 lb. cover / 75 to 216 gsm (uncoated and coated)
Optional Xerox® SquareFold® Trimmer Module (Optional with Standard Finisher – requires Interface Module)	
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm
Sizes	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Convenience Stapler	
Capacity	50 sheets (24 lb. / 90 gsm media)

Xerox® Colour 560/570 Printer

Print	
Print Resolution	Up to 2400 x 2400 dpi
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
Registration	Advanced Registration Technology for tighter control ± 1.2 mm along lead edge ± 2.4 mm side to side
First-print-out Time	PS- A4 LEF Simplex Colour 11.02 seconds / Black and white 9.44 seconds
Print Features	• A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing • Enhanced productivity at 50 ppm colour / 65 ppm black in copy mode; 50 ppm colour / 80 ppm black in network scanning mode • Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish • Makes mobile printing simpler and more convenient • Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm • Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device • Your choice of 2 internal colour servers and 3 powerful external colour servers to best fit your environment: – Xerox® Integrated Colour Server – Xerox® Integrated Fiery Colour Server – EX Print Server, powered by Fiery – Xerox® FreeFlow® Print Server • Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters • Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support
Xerox® Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud(Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Copy	
First-copy-out Time From the Platen: From the DADF:	 As fast as 6.5 seconds colour / 4.1 seconds black and white As fast as 9.6 seconds colour / 7.6 seconds black and white
Warm Up Time	90 seconds (from cold powered down to Ready Copy)
Digital Imaging	Auto colour Auto rotation Image shift Edge erase Auto centreing Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation
Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable per centages

Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto colour selection Area Designation Poster mode Annotation Single/Dual colour Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet Insert Stamping 2-in-1 X Y Zoom Zoom Range 25 to 400% Margin Shift Photo Mode Poster Mode Preset Reduce / Enlarge Programme Ahead Covers Erase, Image Repeat, Image Rotate Interrupt Job Build Job Programme
Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
Input Speed	Document dependent
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Maximum Scan Area	250 sheet capacity • 50 ppm colour / 65 ppm black and white in copy mode; 50 ppm colour / 80 ppm black and white in network scanning mode • Originals up to 11 x 17 in. / A3 in weights from 38 to 105 gsm (16 to 28 lb. bond) • Duplex Automatic Document Feeder (DADF)
Network Print Services	Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release

File Formats	PDF Image Only PDF (Searchable) PDF (Linearised) PDF (A-1 Level A) TIFF V6 JFIF XPS
Document Management Fields (Metadata)	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
Scan Features	Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP Scan via NDS Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to Remote Printer Scan to Fax Server Scan to Multiple Destinations Scan to Documentum Scan to DocuShare Scan to Domino Scan to Hummingbird Scan to Interwoven WorkSite Scan to Live Link Enterprise Server Scan to Microsoft Dynamics GP Scan to MS Exchange web folder Scan to Microsoft SharePoint Scan to SharePoint Portal Server Scan to Thompson ProLaw Scan to Tower TRIM Scan to web URL Scan to Microsoft Network Folder Scan to Exact e-Synergy
Supported Scan Destinations (Standard)	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public)
Scan to Email Features	Colour scanning, Auto Colour, Greyscale, Black and white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job
Supported Scan Destinations (Optional)	Options include Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
Authentication	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
Xerox® ConnectKey™ for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.

Fax (Optional) – One or Three Line Fax Options	
Compatibility	Colour, Auto Colour, Black and white
Maximum Scan Area	11 x 17 SEF
Fax Send Features	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Fax Print Features	Print from USB Storage Device Media Print Unicode Printing
Fax Features	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Device Management	
Xerox® CentreWare® Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox® MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.

Security	
Features	Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication Xerox Secure Access Unified ID System® IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria (Xerox® 560 complete; Xerox® 570 pending)
Xerox Secure Access Unified ID System®(Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to **www.office.xerox.com/software-solutions**.
Print Server	
Xerox® Integrated Colour Server	
Processor	993 MHz
Memory (ESS)	2 GB RAM
System Disk	80 GB Hard Disk Drive
Display	10.4 in. colour touchscreen flat-panel
Page Description Languages	PDF XPS®, PCL® 6 emulation HP-GL2 (direct submission) Adobe® PostScript® 3™ option TIFF JPEG
Operating Systems	Windows® XP SP1 & above (32 & 64 bit) Server 2003 / 2008 (32 & 64 bit) Vista (32 & 64 bit) Windows 7 (32 & 64 bit) Mac OS® 10.4 and above Citrix® Custom driver for UNIX: – AIX® 5 v5.3 – HP-UX® 11.0 / 11i v2 – Solaris® 8/9/10 – Linux® Fedora Core® 1/5 – Red Hat® ES4 – SUSE® 10/11
Features	• Automatic two-sided • Secure print • Delay print • Sample set • Booklet creation • Cover selection • Paper selection by attribute • N-up • Watermarks • Banner sheets • Fit to new paper size • Output tray selection • Optional print from USB Plus more!

Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec option)
	For more information, go to **www.xerox.com/560integrated-colourserver**.
Additional Print Server Options	
Optional Xerox® EXi Integrated Fiery® Colour Server	
Processor	Intel® Pentium® G850 Processor, E200, 2.90 GHz
Memory (ESS)	2 GB
System Disk	500 GB
Print Languages (PDL)	Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9
Features	• Expansive media range – Print everything from postcards to posters. Inline finishing options offer a professional polish with stapling, hole-punching and folding for presentations, brochures, reports and newsletters. • Xerox® Mobile Print – Now printing can be simple, convenient and secure from any email-enabled device, such as a smart phone, iPad® or other tablet. An ideal option for any business with a mobile workforce looking for more flexible printing options. • Customise your print driver settings for economy and efficiency. For example, adjust settings for specific applications, such as always printing emails in black and white. • Scan, print, copy, fax and route files – all at once. Concurrent operations maximise productivity, letting multiple users perform different tasks simultaneously. • Easily share files or introduce electronic archiving with powerful scan capabilities. Create text-searchable files at the device for easy retrieval. Compression technology reduces network load to enable fast transmission. • Create job flow sheets to automatically route documents to predefined locations, including email addresses, fax destinations and FTP/SMB sites. • Remotely manage the device. CentreWare® IS Embedded Web Server automates installation, troubleshooting, feature setup and upgrading. • Internal Auditron sets limits of device features for analysis and billing purposes. Xerox® Standard Accounting provides reports for greater cost control of all device functions. • Smart eSolutions MeterAssistant® collects and submits meter reads and SuppliesAssistant® enables automatic ordering of ink to save time.
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)
	For more information, go to **www.xerox.com/560exi-fierycolourserver**.
Optional Xerox® FreeFlow® Print Server	
Processor	Intel® Core 2 DUO E8400 3.0 GHz
Memory (ESS)	8 GB
System Disk	(2) 250-GB 7200 rpm SATA
Print Languages (PDL)	Adobe PostScript Level 1, 2, 3; Adobe Acrobat® 9.0, PDF 1.8, PDF/X; TIFF, PCL 5c, PCL 6XL, EPS, JPEG
Features	• Fast RIP speeds for Adobe and Microsoft Office files with the Fiery SmartRIP speeds. • Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. • Produce precise, exact colour from all applications, platforms and formats with Fiery ColourWise colour management tools. • Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilities. • Connect to the Fiery from your native Windows file directory and interact seamlessly with your standard Windows experience with the Fiery Bridge. • Make booklets and other documents directly on your desktop with Fiery VUE, a 3-D "visual print application" that guides you through an interactive and intuitive workflow. • Concerned about security? Your administrators will appreciate the Integrated Fiery Colour Server's complete toolset covering all aspects of document and device security.
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)
	For more information, go to **www.xerox.com/560freeflow-printserver**.
Optional EX Print Server, Powered by Fiery	
Processor	Intel® Core i5-2400, 4 Core, PRO80-IV 3.4 GHz (equal or better)
Memory (ESS)	4 GB
System Disk	1 TB
Print Languages (PDL)	Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG

Xerox® Colour 560/570 Printer

Features	• Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colours. This feature also eliminates the need to re-programme jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalised communications and packaging and photo publishing applications. • Fiery ColourWise gives high-quality colour out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Colour Profiler Suite to control and manage colour throughout your workflow. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labor-intensive document composition and imposition tasks even more by using Fiery SeeQuence Impose and Compose's intuitive interface. • Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. • Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless connectivity to Xerox® FreeFlow® for workflow automation.		
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)		
	For more information, go to **www.xerox.com/560ex-printserver**.		
Supplies	**Description**	**Yield**	**Part Number**
Customer Replaceable Items			
Toner Cartridges (Metered)	Black	30,000 pages[3]	006R01521
	Cyan	34,000 pages[3]	006R01524
	Magenta	32,000 pages[3]	006R01523
	Yellow	34,000 pages[3]	006R01522
DMO Toner Cartridges (Sold)	Black	30,000 pages[3]	006R01529
	Cyan	34,000 pages[3]	006R01530
	Magenta	32,000 pages[3]	006R01531
	Yellow	34,000 pages[3]	006R01532
Black Drum Cartridge	1 Cartridge	190,000 pages[3]	013R00663
Colour Drum Cartridge	1 Cartridge per Colour	85,000 pages[3]	013R00664
Charge Corotron	For Black Drum	190,000 pages[3]	013R00650
Fuser	110V 220V	200,000 pages[3] 200,000 pages[3]	008R13102 008R13065
Waste Toner Container	1 Cartridge	50,000 pages[3]	008R12990
Staple Cartridges	For Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	For Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925
	For Standard Finisher with Booklet Maker	5,000 each cartridge	008R13041
Staple Refills	For Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941

To view a product video, visit **www.xerox.com**. Build and configure your own Xerox® Colour 560/570 Printer at **www.buildyourownxerox.com**.

©2013 Xerox Corporation. All Rights Reserved. Xerox®, Xerox and Design®, CentreWare®, FreeFlow®, MeterAssistant®, Scan to PC Desktop®, SMart Kit®, SMARTsend®, SquareFold®, SuppliesAssistant®, Xerox Extensible Interface Platform® and Xerox Secure Access Unifed ID System® and are trademarks of Xerox Corporation in the United States and/or other countries. EFI, Splash, Fiery® and RPX-iii are trademarks of Electronics for Imaging, Inc. Product appearance, build status and/or specifications are subject to change without notice. Updated 7/13